

X : مطابق كارتهمراه

| RE.VE: | DATA | | _ | NAME | ME | _ | Description | | | | Machine | | Core Hardness(HRC) | |
|---------------|----------|--------------------|-----------------|--------|--------------------|------------------------|-------------|-----|--------------|-----------------|----------------|------------------------------|--------------------|--|
| T \ C. \ V C. | BATTA | | | TO WIL | | | | | | | Material | | Surface Hardness | |
| Standard List | | | Part N | 10 | | | | | | Dia.of Material | | T.S (Mpa) | | |
| | | | - uiti | | | | | | | diameter blank | | Y.S (Mpa) | - | |
| Dimension | DIN 60: | 3 P | Part na | ıme | M8*1.25*60-6g | | | | | length blank | | Proof Load | | |
| Mechanical | DIN 898 | -1 г | DWG.I | NO | TP603/08(60)/00 | | | | | Weight | | EL (%) | | |
| | | | D V V O.1 | • | 1. 222, 30(00), 00 | | | | | | Rod Production | | Type Coating | |
| Coating | | | | N | ame | Data | Scale | 2:1 | پیچیزد | سپنـد | process | | Color | |
| - . | 100 4750 | | Drawn Cheked | n S. | Zabihi | 02/07/29 | Safety | | SEPAND PITCH | Quality Class | | Salt Spray To Sediment Red | | |
| Tolerances | ISO 4759 |) -1 ├─ | | | S.Zabihi 02 | 02/07/20 | Regularity | | | Coating | | Salt Spray To Sediment Withe | | |
| Other | | | Спеке | eu 5. | Zabini | | | | | | | Α.Τ | • | |
| Standard | | | Confirmed | | rahmand | and 02/07/29 Unit : mm | | | | Customer 1 | Name : | | | |