

| RE.VE: | DATA | | NAME | T | _ | Description | on | | | Machine | | Core Hardness | 200-300HV |
|------------|-----------|------|----------|-------------------------------|----------|-------------|------------|-----------------|-----------------|----------------|-------------------------|------------------------------|-----------|
| | 27 | | | | | ' | | | | Material | | Surface Hardness | |
| Stan | dard List | Part | NO | 30011301 | | | | Dia.of Material | | T.S (Mpa) | | | |
| Otan | - LIOC | | | 23311001 | | | | | | diameter blank | | Y.S (Mpa) | |
| Dimension | Dimension | | ame | | | | | | length blank | | Proof Load (Mpa) | | |
| Mechanical | | DWG | NO | | | | | | | Weight | | EL (%) | |
| 0 " | 0 " | | | | | | | | Rod Production | | Type Coating | | |
| Coating | | | N | lame | Data | Scale | 2/1 | ، پيچ يــزد | سپند | process | | Color | |
| Tolerances | | Drav | n B.Sa | lehizade | 01/10/07 | Safety | П | | | Quality Class | | Salt Spray To Sediment Red | |
| | | Obst | | | 04/40/07 | Pogularity | _ | SEPAND | PITCH | Coating | | Salt Spray To Sediment Withe | |
| Other | | Chek | | | | Regularity | Ц | co. | | C 4 | ■T | 1 ' 1 | |
| Standard | Standard | | med K.Fa | K.Farahmand 01/10/07 Unit: mm | | | CO. | | Customer Name : | | گــروه صــنعتی انتخــاب | | |